



Lubell LL-1424HP Underwater Acoustic Transducer

High-Power Broadband Piezoelectric Underwater
transducer for Military and Scientific Applications

Comes installed in cage - click pic for view

SPECIFICATIONS

- **PRICE:** USD \$8330
- **Frequency Range:** 200Hz - 9kHz
- **SPL:** 197dB/uPa/m @ 600Hz (80V rms applied at cable end)
- **Maximum Voltage:** 80 Vrms
- **Duty Cycle:** 100%/10A, 50%/14A
- **Impedance:** 8 ohms nominal (including AC1424HP xfmr box)
- **Depth Rating:** 6' - 40'
- **Dimensions:** 16.5" x 16.5" x 16.5"
- **Ducer/Cage Wt:** 61 lbs/air, 33 lbs/water
- **Finish:** 10-mil epoxy on MIL-C-5541 Class 1-A (transducer); 304SS cage
- **Connector:** Seacon [XSEE3BCR](#)
- **Cable:** Seacon [XSEE3CCP](#) molded to one end of 75 feet [14/3 SO cable](#) (15 lbs)
- **Data:** [Guide](#), [TVR](#), [SPL](#), [Z](#), [tabular](#)
- **Included:** Protective cage, [AC1424HP](#) bridging xfmr box, 75 foot cable
- **Option:** Add Swagelok SS-400-1-OR (\$79)
- **Warranty:** 2 year limited
- **Amplifier:** [CDi2000](#) (USA) or CDi2000-E60 (EU) \$1373

lubell_labs@wowway.com

Tel: (614) 725-2701, 9:00am-5:00pm EST

[Printable PDF brochure \(47KB\)](#)

[Complete instructions and test data \(3.16MB\)](#)

DESCRIPTION

The LL-1424HP is a piezoelectric underwater acoustic transducer designed for general purpose military and scientific applications. The LL-1424HP may also be used as an underwater speaker when high power is required.

The LL-1424HP has a useful frequency range of 200Hz-9kHz, a maximum SPL of 197dB/uPa/m @ 600Hz w/80V rms applied, and a nominal impedance of 8 ohms. Because of variation between cast parts, the uniformity of response cannot be guaranteed but is typically +/- 1.5dB from published values. The LL1424HP is provided with an AC1424HP bridging transformer box allowing connection to amplifiers up to 2500 watts at 4 ohms bridged mono.

The LL-1424HP is built to withstand ocean environments by virtue of its 10 mil epoxy finish and cage mounting system. The LL-1424HP is fitted with a Seacon bulkhead connector and includes a mating 75 foot Seacon cable.

