

ZX1



It's your music, your voice, your message.

You need a speaker that can reproduce every note, every inspirational word

and every nuance of your style. Introducing ZX1. Compact, lightweight, yet high performance, ZX1 is a reflection of the needs of the high-speed,

time-crunched, high-tech lifestyle you lead. Its versatility is matched only by your imagination, and its look is pure beauty. So while your audience may not be fully aware

of why you sound incredible, you'll know it's because you

chose the very best . . .

ZX1



ZX1 offers a wide array of mounting options including an integrated pole mount and removable rubber feet that hide M8 mounting studs. Dual NL4 connectors and an ergonomic molded carrying slot make **ZX1** perfect for portable music, AV rental and mobile audio applications.

ZX1 shines in monitor wedge applications, especially where the reproduction of vocal frequencies is crucial. Its asymmetrical cabinet design means you simply have to put **ZX1** on its side to achieve a 45° monitor angle. And with the ability to rotate its 90° x 50° horn, you can adjust the dispersion pattern to suit your unique application.

| | ZX1-90 Portable Version | ZX1i-90 Fixed Install Version | ZX1i-100 Fixed Install Version | ZX1i-100t 70v/100v Version |
|--|--|--|--|--|
| Frequency Response⁽¹⁾ (-3 dB) | 60 Hz - 20 kHz | 60 Hz - 20 kHz | 60 Hz - 20 kHz | 60 Hz - 20 kHz |
| Frequency Range⁽¹⁾ (-10 dB) | 48 Hz - 20 kHz | 48 Hz - 20 kHz | 48 Hz - 20 kHz | 48 Hz - 20 kHz |
| Axial Sensitivity⁽¹⁾ | 94 dB (1W/1m) | 94 dB (1W/1m) | 92 dB (1W/1m) | 92 dB (1W/1m) |
| Maximum Calculated SPL | 123 dB | 123 dB | 121 dB | 121 dB |
| Horizontal Coverage | 90° or 50° | 90° or 50° | 100° | 100° |
| Vertical Coverage | 50° or 90° | 50° or 90° | 100° | 100° |
| System Power Handling | 200W Continuous, 400W Program | 200W Continuous, 400W Program | 200W Continuous, 400W Program | 200W Continuous, 400W Program |
| LF Transducer | EV8L, 8 in (203mm) Driver | EV8L, 8 in (203mm) Driver | EV8L, 8 in (203mm) Driver | EV8L, 8 in (203mm) Driver |
| HF Transducer | DH2005, 1 in. (25.4mm) Exit Compression Driver | DH2005, 1 in. (25.4mm) Exit Compression Driver | DH2005, 1 in. (25.4mm) Exit Compression Driver | DH2005, 1 in. (25.4mm) Exit Compression Driver |
| Nominal Impedance | 8 Ohms | 8 Ohms | 8 Ohms | 8 Ohms |
| Pole Mount | Included | N/A | N/A | N/A |
| Transformer Taps | N/A | N/A | N/A | 6.5, 12.5, 25, 50, 100 watts 70/100v |
| Connectors | Two NL4 Connectors | 4-Pin detachable Phoenix style | 4-Pin detachable Phoenix style | 4-Pin detachable Phoenix style |
| Overload Protection | Full protection - all modes | Full protection - all modes | Full protection - all modes | Full protection - all modes |
| Mounting System | Four M8 studs on bottom of speaker | QuickSAM™ Heavy-Duty Strong-Arm Mounting Bracket | QuickSAM™ Heavy-Duty Strong-Arm Mounting Bracket | QuickSAM™ Heavy-Duty Strong-Arm Mounting Bracket |
| Built-In Monitor Angle | Yes | No | No | No |
| Available Colors | Black | Black/White | Black/White | Black/White |
| Included Accessories | None | QuickSAM™ Mount | QuickSAM™ Mount | QuickSAM™ Mount |
| Dimensions (H x W x D) | 17.75" x 11.12" x 10.35" 451mm x 282mm x 263mm | 17.75" x 11.12" x 10.35" 451mm x 282mm x 263mm | 17.75" x 11.12" x 10.35" 451mm x 282mm x 263mm | 17.75" x 11.12" x 10.35" 451mm x 282mm x 263mm |
| Net Weight | 8.4 kg (18.5 lbs) | 8.4 kg (18.5 lbs) | 8.4 kg (18.5 lbs) | 10.4 kg (23.0 lbs) |
| Shipping Weight | 10.2 kg (22.5 lbs) | 10.2 kg (22.5 lbs) | 10.2 kg (22.5 lbs) | 12.3 kg (27.0 lbs) |

(1) Half-space measurements

The Complete ZXI Family

The ZXI is part of a complete compact speaker system product line with models for fixed installation distributed systems.



Americas

Telex Communications Inc.
12000 Portland Ave South,
Burnsville, MN 55337, USA
USA — Phone: 1-800-392-3497, Fax: 1-800-955-6831
Canada — Phone: 1-866-505-5551, Fax: 1-866-336-8467
Latin America — Phone: 1-952-887-5532, Fax: 1-952-736-4212

Europe, Africa & Middle-East

Germany: EVI Audio GmbH.
Hirschberger Ring 45, D 94315,
Straubing, Germany
Phone: +49 9421 706-0, Fax: +49 9421 706-265

France: EVI Audio France S.A.,
Parc de Courcerin,
Allée Lech Walesa,
F 77185 Lognes, France
Phone: +33 1-6480-0090
Fax: +33 1-6006-51-3

UK: Shuttlesound,
4 The Willows Centre,
Willow Lane, Mitcham,
Surrey CR4 4NX, UK
Phone: +44 208 646 7114
Fax: +44 208 245 5666

Asia & Pacific Rim

Japan: EVI Audio Japan Ltd.
5-3-8 Funabashi, Setagaya-Ku,
Tokyo, Japan 156-0055
Phone: +81 3-5316-5020,
Fax: +81 3-5316-5031

China: Telex EVI Audio (Shanghai) Ltd.
Room 2210-2215,
Tower B, Far East International Plaza
No. 317, Xianxia Road,
Shanghai, China, PC: 200051
Phone: +86 (21) 6235-1677
Fax: +86 (21) 6235-1676

Hong Kong: Telex EVI Audio (HK) Ltd.
Unit 5, 1/F, Topsail Plaza
11 On Shum Street
Shek Mun, Shatin HK
Phone: +852 2351-3628, Fax: +852 2351-3329

Singapore: Telex Pte. Ltd.
3015A Ubi Road 1, 05-10
Kompong Ubi Industrial Estate, Singapore 408705
Phone: +65 6746-8760, Fax: +65 6746-1206

Live For Sound™
www.electrovoice.com

