CHIAYO





FEATURES

- Ruggedly built compact ABS speaker enclosure.
- 200W Class-D amplifier to power a 8" full-range driver.
- Up to 4 diversity receiver modules with 100 frequencies.(optional)
- Scan and Sync button for quick and simple mic channel set-up.
- MIC 1 and 2 are XLR/Φ6.3mm combo jack connectors for microphone and line inputs with individual volume control and a MIC/LINE level switch.
- LINE IN (\$\$\Phi3.5mm jack) with volume control.
- SPEAKER OUT (Φ6.3mm jack) for an external 8Ω passive speaker with volume control.
- LINE OUT (Φ6.3mm jack) for external audio recording.
- 2-band equalizer (BASS / TREBLE) for all audio inputs.
- VOICE PRIORITY automatically ducks music when a microphone is used (switchable).
- REVERB with bypass for wired and wireless microphones (switchable).
- LOUDNESS function boosts bass/treble performance (switchable).
- Digital limiter prevents output distortion, with 6-step LED audio meter indicator.
- Smart charging circuit with 4-step LED battery indicators and charging LED.
- User friendly battery compartment design for simple battery replacement.
- Tripod stand mountable with ST-50.
- More than 12 hours operating time per charge with lithium battery and 10 hours with Lead-Acid battery.
- 2 power modes: Internal Rechargeable battery & DC jack.
- DC power output 12V for external device.



** Specifications and design are subject to change without prior notice.

CHIAYO ELECTRONICS CO., LTD.

OFFICE: No. 30, Lane 27, Section 4, Jen-Ai Road, Taipei 10685, Taiwan TEL: 886-2-2741-5741 FAX: 886-2-2752-5242

FACTORY: No. 88, Chung-Hsiao Street 2, Chiayi 60080, Taiwan TEL: 886-5-271-1000 | FAX: 886-5-276-7611 | WEB: www.chiayo.com.tw | E-mail: sales@chiayo.com.tw

CHIAYO

SPECIFICATIONS

Model	STAGE MAN	
Max power output	200W, 4Ω load (class-D)	
Speaker system	8" full range	
Audio input	Mic/Line in x2 (COMBO), Line in (3.5mm)	
Audio output	Line out, External speaker (with volume control)	
T.H.D.	< 0.5%	
Freq. response	50Hz-20KHz±3dB	
Antenna	Built-in	
Power supply	100-240V AC, 30-32V DC/4A	
Battery type	Lead-Acid	Lithium
Battery spec	12V/5A	29.4V/7.8A
Battery Q'ty	2	1
Standby time	5-6 hours in music, >10 hours in speech	8-10 hours in music, >12 hours in speech
Charging time	about 6 hours	about 8 hours
Dimension (mm)	424(H) x 290(W) x 250(D)	
Weight (kg)	10.8	7.8

** Specifications and design are subject to change without prior notice.